



TUCA 15 / 19

FLUSH MOUNT CEILING

location:
DAMP

SPECIFICATIONS:

DESCRIPTION

Flush-mounted ceiling fixture, featuring handcrafted glass diffuser.

LAMPING

LED: 16W Integrated source, 120V, dimmable, 85+ CRI, 3000°K CCT, 1600 lumens, 30,000 hours, included. (For Tuca 15 only)

LED: 20W Integrated source, 120V, dimmable, 85+ CRI, 3000°K CCT, 2200 lumens, 30,000 hours, included. (For Tuca 19 only)

DIFFUSER

Handcrafted glass diffuser in Opal Matte with metallic foil ring.

Tuca 15: 15.5" Dia. x 3.25" H

Tuca 19: 19.25" Dia. x 3.5" H

CONSTRUCTION

Glass diffuser is secured to fitter with "twist & lock" bayonet action. Stamped aluminum fitter is powder coated white.

MOUNTING

Installs directly to a 4" octagonal outlet box, centered on fixture.

90°C supply wire required for incandescent lamping.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).



OPAL/SILVER FOIL (TUCA19SFC)

TUCA15GFC
OPAL/GOLD FOIL



For ordering information, see next page


All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 3/17




ORDERING:

Tuca 15: _____



FIXTURES		LAMP OPTIONS	
TUCA15GFC	15.75" Gold Foil	LED	16W LED 120V
TUCA15SFC	15.75" Silver Foil		1600 lumens

Tuca 19: _____



FIXTURES		LAMP OPTIONS	
TUCA19GFC	19.25" Gold Foil	LED	20W LED 120V
TUCA19SFC	19.25" Silver Foil		2200 lumens

Ex. TUCA15GFC-LED
Tuca 15 LED Ceiling, Gold Foil Shade

Project Information: