# **TRULUX** RF RGB+WW USB Remote Control



PROJECT:	TYPE:
LOCATION:	CAT:
R G B W O A P O O O O O O O O O O O O O O O O O	B B A D A B A B A B A B A B A B A B A B

#### Description

Trulux RF RGB/RGB+WW hand-held, USB rechargeable remote control for RGB/RGB+WW light control; 1-8 zone operation and 10 preset levels.

#### **Features**

- Features On/Off and 'back' button
- Ten preset color changing functions plus pause function
- One-button control for R, G, B, and W; hold for full range dimming (1-100%)
- Radio frequency (RF) signal range up to 65 feet
- Control multiple receivers in multiple zones
- Battery operated (USB rechargeable lithum battery included)
- Requires Trulux RF receiver for operation (sold separately)

### Mounting

Hand-held remote includes wall-mount caddy

#### **Applications**

Dimming, CCT, scene control, and zone control for RGB/RGB+WW

#### Warranty


3 years

### Technical Information





Voltage	3.6V DC Operation voltage (battery operated)
Battery Type	USB Rechargeable lithium (included)
Frequency	916.5MHz RF wireless
Operating Temperature	0° - 40°C
Relative Humidity	8% - 80%
Rating	FCC Compliant, RoHS Compliant, dry location



# Required Receivers

Part Number	Description	Application	Input	Current	Output	Listing	Dimensions
REC-5A-4Z	Trulux RF Constant Voltage Receiver	Dry location	12-36V DC	4x5A	4x(60-180)W	RoHS	7-1/16" x 1-13/16" x 6-23/32" (178.9mm x 45.5mm x 18.6mm)

## Ordering Information



### RF-RGBW-USB includes:

(1) Trulux RGB+WW Remote Control (requires Trulux receiver)

Example Part # RF-RGBW-USB

|--|